

## 100

### Adjustable Wire Stripper & Cutter

- Strips and cuts insulated wire sizes from #22 AWG (0.65 mm) to #10 AWG (2.6 mm)
- Effective for stripping/scoring fiber optic jackets and buffer tubing
- Stop screw adjusts easily to fit wire size
- Ground and unground cutting surface versions available
- Soft plastic coated handles
- Made in the U.S.A.
- Length: 5.125 in (130.18 mm)
- Weight: 2.5 oz (71 g)
- **Also available with opening spring and closing lock feature (Model #101-S)**
- Part No.: 80300



## 103-S

### Adjustable Wire Stripper & Cutter with cam adjustment

- Strips and cuts insulated wire sizes from #22 AWG (0.65 mm) to #10 AWG (2.6 mm)
- Cam adjusts easily to fit wire size
- Pressure is against the cam not on the set screw
- Opening spring and closing lock feature
- Ideal for all applications
- Ground and unground versions available
- Soft plastic coated handles
- Made in the U.S.A.
- Length: 5.375 in (136.53 mm)
- Weight: 2.5 oz (71 g)
- Part No.: 80315



## 111-TAS

### Thumb Adjustable Wire Stripper & Cutter

- Effective for stripping & cutting insulated wire sizes from #22 AWG (0.65 mm) to #10 AWG (2.6 mm)
- Scalloped handles ergonomically designed for ease of use and optimum operator comfort
- Patented mechanism allows for full range adjustment
- Finger operated stop, adjusts easily for manual adjustment of jaws without additional tools
- Unique spring mechanism holds the jaws and stripping surfaces in a normally open position, permitting ease of operation in repetitive stripping applications
- Once set, the operating pressure is encapsulated between the cam and pivoting tool arm, allowing for maximum operator leverage
- All cutting surfaces are precision formed, hardened, tempered and ground assuring clean smooth strips
- U.S. Patent No.: 6,418,817
- Length: 5.4 in (137 mm)
- Weight: 2.2 oz (62 g)
- Part No.: 80735

