

NO-NIK®

Wire Strippers

- The premier precision wire stripper for removing insulation from solid or stranded wire without nicking or scratching the conductor
- Stripping blade diameters range from 0.008 in to 0.054 in (.203 mm to .323 mm)
- Stripping apertures are accurate to -0 in, + 0.0005 in (.0127 mm)
- Simple operation
- Insulation being removed protects conductor from the stripping blades
- No adjustments needed; each tool is made to strip specific wire sizes
- Handles are color-coded to tool size for easy identification
- Stripping Blade Diameter Marking and Indicating Arrow:
 - Stripping blade diameter clearly marked on plastic head.
 - Arrow indicates direction pressure should be applied when stripping
- Made in the U.S.A.
- Length: 5.3 in (135 mm)
- Weight: 1.6 oz (45 g)



Wire Stripper Selection Chart

Model	Part Number	Cutting Diameter*	Handle Color	AWG	Wire Construction	Nominal Conductor Diameter	
						Inches	mm
NN044	46215	.044	Dark Brown	18	Single	.0403	1.0236
NN054	46217	.054	Clear		Stranded	.044	1.1176
NN034	46211	.034	Pink	20	Single	.0320	.8128
NN037	46213	.037	Grey				
NN037	46213	.037	Grey		Stranded	.035	.889
NN044	46215	.044	Dark Brown				
NN028	46206	.028	Black	22	Single	.0253	.64262
NN031	46209	.031	Tan				
NN031	46209	.031	Tan		Stranded	.028	.7112
NN034	46211	.034	Pink				
NN023	46202	.023	Maroon	24	Single	.0201	.511
NN025	46204	.025	Light Green				
NN025	46204	.025	Light Green		Stranded	.022	.5588
NN028	46206	.028	Black				
NN018	46198	.018	Yellow	26	Single	.0159	.404
NN021	46200	.021	Royal Blue				
NN021	46200	.021	Royal Blue		Stranded	.017	.4318
NN023	46202	.023	Maroon				
NN014	46194	.014	Dark Green	28	Single	.0126	.320
NN016	46196	.016	Orange				
NN016	46196	.016	Orange		Stranded	.014	.3556
NN018	46198	.018	Yellow				
NN012	46192	.012	White	30	Single	.0100	.254
NN014	46194	.014	Dark Green				
NN014	46194	.014	Dark Green		Stranded	.011	.2794
NN016	46196	.016	Orange				
NN010	46190	.010	Light Blue	32	Single	.0080	.2032
NN012	46192	.012	White				
NN010	46190	.010	Light Blue		Stranded	.009	.2286
NN012	46192	.012	White				
NN008	46188	.008	Red	34	Single	.0063	.160
NN010	46190	.010	Light Blue		Stranded	.007	.1778
NN010	46190	.010	Light Blue				
NN008	46188	.008	Red	36	Single	.0050	.127
NN008	46188	.008	Red		Stranded	.006	.1524

* Proper selection depends upon type of insulation and insulation construction.