

CABLE TYPE : RG 11A/ U
SPECIFICATION : MIL C-17
APPLICATION : Used in radio communication and data transmission systems as connection cable.
CONSTRUCTION : 7x 0,73 mm Electrolytic stranded copper conductor 7,25mm. Solid PE 95% braiding of copper wire screen 10,30mm. Black PVC outer sheath Cable weight 153 Kg/Km. Standart packing 100-500-1000m

TECHNICAL DATA

| | | | | | |
|----------------------------------|------------------|-----|-----|-----|------|
| 1 . Capacitance | : 67 pF/m. | | | | |
| 2 . Impedance | : 75+3 ohm | | | | |
| 3 . Velocity Ratio | : 0,66 | | | | |
| 4 . Insulation Resistance | : > 2000 Mohm km | | | | |
| 5 . Working Temperature | : -40 0C+70 0C | | | | |
| 6 . Working Voltage | : 5 kV | | | | |
| 7 . Test Voltage | : 8 kV | | | | |
| 8 . Min. Bending Radius | : 15 xD | | | | |
| 9 . Attenuation : | | | | | |
| Frequency (MHz) | 100 | 200 | 500 | 800 | 1000 |
| Attenuation (dB/100m) | 7 | 9,7 | 16 | 21 | 24 |

